


Surface Mount Transformers/Inductors, Gapped and Ungapped, Custom Configurations Available



ELECTRICAL SPECIFICATIONS

(Multiple winds are connected in parallel)

Inductance Range: 10 μ H to 150 000 μ H, measured at 0.10 V RMS at 10 kHz without DC current, using an HP 4263 or HP 4284A impedance analyzer

DC Resistance Range: 0.02 Ω to 46.2 Ω , measured at + 25 °C $\pm$ 5 °C


Rated Current Range: 3.20 amps to 0.17 amps

Dielectric Withstanding Voltage: 500 V RMS, 60 Hz, 5 seconds


RoHS
COMPLIANT

DIMENSIONS in inches [millimeters]

Pad Layout



Dimensional Outline



Foot print Diagram

NOTE: Pad layout guidelines per MIL-STD- 275E (printed wiring for electronic equipment).

Tolerances: xx $\pm$ 0.01" [$\pm$ 0.25 mm], xxx $\pm$ 0.005" [$\pm$ 0.12 mm].

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	IND. (μ H)	IND. TOL.	SCHEMATIC LETTER	DCR MAX. (Ohms)	MAX. RATED* DC CURRENT (Amps)	SATURATING CURRENT** (Amps)
Ungapped Models (A)						
LPE6855ER151NU	150	$\pm$ 30 %	A	0.28	0.84	N/A
LPE6855ER221NU	220	$\pm$ 30 %	A	0.34	0.76	N/A
LPE6855ER331NU	330	$\pm$ 30 %	A	0.41	0.69	N/A
LPE6855ER471NU	470	$\pm$ 30 %	A	0.49	0.63	N/A
LPE6855ER681NU	680	$\pm$ 30 %	A	0.59	0.57	N/A
LPE6855ER102NU	1000	$\pm$ 30 %	A	0.72	0.52	N/A
LPE6855ER152NU	1500	$\pm$ 30 %	A	0.88	0.47	N/A
LPE6855ER222NU	2200	$\pm$ 30 %	A	1.07	0.43	N/A
LPE6855ER332NU	3300	$\pm$ 30 %	A	1.31	0.39	N/A
LPE6855ER472NU	4700	$\pm$ 30 %	A	1.56	0.35	N/A
LPE6855ER682NU	6800	$\pm$ 30 %	A	1.88	0.32	N/A
LPE6855ER103NU	10 000	$\pm$ 30 %	A	7.17	0.16	N/A
LPE6855ER153NU	15 000	$\pm$ 30 %	A	8.78	0.15	N/A
LPE6855ER223NU	22 000	$\pm$ 30 %	A	10.6	0.14	N/A
LPE6855ER333NU	33 000	$\pm$ 30 %	A	13.0	0.12	N/A
LPE6855ER473NU	47 000	$\pm$ 30 %	A	15.5	0.11	N/A
LPE6855ER683NU	68 000	$\pm$ 30 %	A	18.7	0.10	N/A
LPE6855ER104NU	100 000	$\pm$ 30 %	A	37.7	0.07	N/A
LPE6855ER154NU	150 000	$\pm$ 30 %	A	46.2	0.06	N/A
Gapped Models (B)						
LPE6855ER100MG	10	$\pm$ 20 %	B	0.02	3.21	3.375
LPE6855ER150MG	15	$\pm$ 20 %	B	0.03	2.90	2.790
LPE6855ER220MG	22	$\pm$ 20 %	B	0.04	2.64	2.325
LPE6855ER330MG	33	$\pm$ 20 %	B	0.05	2.12	1.910
LPE6855ER470MG	47	$\pm$ 20 %	B	0.08	1.73	1.610
LPE6855ER680MG	68	$\pm$ 20 %	B	0.12	1.41	1.350
LPE6855ER101MG	100	$\pm$ 20 %	B	0.15	1.28	1.120
LPE6855ER151MG	150	$\pm$ 20 %	C	0.23	1.02	0.915
LPE6855ER221MG	220	$\pm$ 20 %	D	0.35	0.83	0.757
LPE6855ER331MG	330	$\pm$ 20 %	D	0.55	0.67	0.620
LPE6855ER471MG	470	$\pm$ 20 %	E	0.82	0.54	0.520
LPE6855ER681MG	680	$\pm$ 20 %	F	1.23	0.45	0.433
LPE6855ER102MG	1000	$\pm$ 20 %	F	1.89	0.36	0.358
LPE6855ER152MG	1500	$\pm$ 20 %	F	2.90	0.29	0.292
LPE6855ER222MG	2200	$\pm$ 20 %	F	4.50	0.23	0.242
LPE6855ER332MG	3300	$\pm$ 20 %	F	5.50	0.21	0.197
LPE6855ER472MG	4700	$\pm$ 20 %	F	8.30	0.17	0.166

* DC current that will create a maximum temperature rise of 30 °C when applied at + 25 °C ambient. ** DC current that will typically reduce the initial inductance by 20 %.

UNGAPPED MODELS: Highest possible inductance with the lowest DCR and highest Q capability. Beneficial in filter, impedance matching and line coupling devices.

GAPPED MODELS: Capable of handling large amounts of DC current, tighter inductance tolerance with better temperature stability than ungapped models. Beneficial in DC to DC converters or other circuits carrying DC currents or requiring inductance stability over a temperature range.


DESCRIPTION

LPE	6855	1000 μ H	$\pm$ 30 %	A	ER	e2
MODEL	SIZE	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	CORE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER

L	P	E	6	8	5	5	E	R	1	0	2	N	U
PRODUCT FAMILY				SIZE		PACKAGE CODE		INDUCTANCE VALUE			TOL.	CORE	

NOTE Series is also available with SnPb terminations by using package code RY for tape and reel (in place of ER) or SM for bulk (in place of EB).

SCHEMATIC (TOP VIEW)

NOTE: Schematic A is for Ungapped LPE Series

ENVIRONMENTAL PERFORMANCE

TEST	CONDITIONS
Thermal Cycling	Withstands - 55 °C to + 125 °C
Operating Temperature	- 55 °C to + 125 °C
High Humidity	85 %
Soldering Heat	Tested to + 230 °C
Mechanical Shock	Per MIL-STD-202, Method 213 (100G)
Vibration	Per MIL-STD-202, Method 204 (20G)
Solderability	Per industry standards

* Must be checked in end use application

PART MARKING

- Vishay Dale
- Date code
- Marking code (Suffix of model #)
- Pin 1 indicator

PACKAGING**TAPE SPECIFICATIONS:**



Carrier Tape Type: Conductive
 Cover Tape Type: Anti-static
 Cover Tape Adhesion to Carrier: 40 ± 30 grams

REEL SPECIFICATIONS:

Diameter (flange): 13" [330.2 mm]
 Maximum Width (over flanges): 1.197" [30.4 mm]

STANDARDS: All embossed carrier tape packaging will be accomplished in compliance with latest revision of EIA-481 "Taping of Surface Mount Components for Automatic Placement".

MODEL	TAPE WIDTH	COMPONENT PITCH	UNITS PER 13 INCH REEL
LPE-6855	32 mm	20 mm	450

Tape and Reel Orientation



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.